



HEALTH AND SAFETY DATA SHEET

1. IDENTIFICATION OF PRODUCT AND SUPPLIER

Product Name Treadmaster Cleaner
Supplier Tiflex Limited
Tiflex House
Liskeard, Cornwall
PL14 4NB.
Telephone +44 (0)1579 320808
Fax +44 (0)1579 320802

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Approx. %	Hazard Classification and Risk Phrases
Isopropanol (Propan-2-ol)	67-63-0	1 - 10 %	F; R11, Xi; R36, R67

3. HAZARDS IDENTIFICATION

Main Hazards: No Significant hazard
Eyes: May cause irritation.
Skin: May cause irritation.
Ingestion: May cause irritation to mucous membranes.

4. FIRST AID MEASURES

Eye Contact: Rinse eye immediately with plenty of water, continue to rinse for at least 15 minutes whilst holding the eye lids apart. Seek medical attention if symptoms persist.
Skin Contact: Wash off skin immediately with plenty of soap and water. Remove any contaminated clothing and launder before re-use. Seek medical attention if symptoms persist.
Ingestion: DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

5. FIRE FIGHTING MEASURES

Extinguishing media: Use extinguishing media appropriate to the surrounding fire conditions.
Fire Hazards: Burning produces irritating, toxic and obnoxious fumes.
Protective equipment: Wear suitable respiratory equipment when necessary.

6. SPILLAGE AND ACCIDENTAL RELEASE MEASURES

Environmental precautions: Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods: Absorb with inert, absorbent material. Transfer into a suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.

Storage: Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTIVE EQUIPMENT

Exposure limits:

Isopropanol	WEL 8 hr limit ppm:	400	WEL 8 hr limit mg/m3:	999
(Propan-2-ol)	WEL 15 min limit pp	500	WEL 15 min mg/m3:	1250

Engineering measures: Ensure adequate ventilation of the working area.

Hand protection: Chemical resistant gloves (PVC)

Eye protection: In case of splashing, wear: Approved safety goggles.

Protective equipment: Wear protective clothing.

9. PHYSICAL CHARACTERISTICS

Description: Liquid.
Colour: Green
Odour: Characteristic
Boiling point: 100°C
Relative density; 1.011
Water solubility: Miscible in water.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Direct sunlight. DO NOT allow to freeze. Heat.

11. TOXICOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

General Information: Dispose of in compliance with all local and national regulations.

14. TRANSPORTATION INFORMATION

Further Information: The product is not classified as dangerous by carriage.

15. REGULATORY INFORMATION

Risk phrases: NSH - No significant hazard.

16. OTHER INFORMATION

Text of risk phrases in Section 2.	R11	Highly flammable.
	R36	Irritating to eyes.
	R67	Vapours may cause drowsiness.

Information on this Health and Safety Data Sheet is drawn from a variety of sources, including raw material suppliers data, and other published sources.

This information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy his/herself as to the suitability of such information for his/her own particular use. This product falls within the scope of the Control of Substances Hazardous to Health (COSHH) Regulations. Users are reminded that this document does not in itself constitute an assessment of workplace risk as required by those regulations.